

Micro Joystick

Instructions



Quite simply - the simplest joystick ever!

All functions are controlled with the joystick which has 3 modes;

- 1. Pan & Tilt
- 2. Zoom & Focus
- 3. Menu Scroll & select

The modes are changed with the touch-down switch on the joystick. You can either *tap* the switch or *hold down* the switch.

A *tap* is less than 0.5 second A *hold down* is more than 0.5 second

The joystick powers up in **Pan & Tilt** mode. To toggle between **Pan & Tilt** mode and **Zoom & Focus** mode, just *tap* the joystick switch.

To enter Menu Scroll mode, *hold down* the joystick switch. Then use the joystick to navigate the menu.

To exit Menu Scroll mode, hold down the joystick switch.

Connections;

DC jack : 12 - 35vXLR4: on a flying lead. This has both power & data for a remote head.

Note: The supplied power supply is 12w. This is enough for some cameras but not for others. Check the power consumption of the camera you are using. Include the lens motors if fitted. If needed, use a 2nd power supply near to the camera with a break-out cable.

There is a connector on the PCB inside which can be used to connect a **Remote Camera Panel** or other equipment into the system. When data is being received the LED will flash.

Note: Not all functions apply to all camera models. Check camera specification for applicable functions.

Function List

Home Menu

Pan & Tilt Control

Тар

Zoom Focus Menu

Zoom & Focus

Hold Down

Menu Scroll

Joystick up/Down to Scroll Joystick Left/Right to change value

Head Functions

Pan Gear Tilt Gear Josytick Ramp (Ramp up & Ramp down together) Head Select 1 - 32 Preset Store GoTo Preset Tally On/Off Set Home

User Setup

Change Head ID. Reset Head to Factory Calibrate Joystick Head Reverse. Pan/Tilt directions, **Swap Iris & Focus**, Zoom direction, Focus direction Select Camera Model - Marshall / Dreamchip Camera Format – HD/4K, 24/25/29.95/50/60, i/p etc. Reset ALL Heads to ID #01

CCU Functions

Iris – Auto / Manual / Adjust Gain Shutter Dynamic Noise Reduction (DNR) Detail Gamma Master Pedestal (MPED) White Balance – Push, Manual, Full Auto White, 3/k2, 5k6 Red Gain Blue Gain Auto Focus On/Off

Note: Not all CCU functions are available on all cameras. Check camera data sheet for available functions.

Further CCU functions are available but require a **Remote Camera Panel**. Ask your dealer or visit website for details.

www.br-remote.com

Tel: +44 (0)1590 622440

admin@br-remote.com